

IEEE HOME | SEARCH IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE


[Membership](#) [Publications/Services](#) [Standards](#) [Conferences](#) [Careers/Jobs](#)
IEEE Xplore®
RELEASE 1.8

 Welcome
United States Patent and Trademark Office

[Help](#) [FAQ](#) [Terms](#) [IEEE Peer Review](#)
[Quick Links](#)

Welcome to IEEE Xplore®

- ☐ Home
- ☐ What Can I Access?
- ☐ Log-out

Tables of Contents

- ☐ Journals & Magazines
- ☐ Conference Proceedings
- ☐ Standards

Search

- ☐ By Author
- ☐ Basic
- ☐ Advanced
- ☐ CrossRef

Member Services

- ☐ Join IEEE
- ☐ Establish IEEE Web Account
- ☐ Access the IEEE Member Digital Library

IEEE Enterprise

- ☐ Access the IEEE Enterprise File Cabinet

Print Format

 Your search matched **19** of **1099723** documents.

 A maximum of **500** results are displayed, **15** to a page, sorted by **Relevance Descending** order.

Refine This Search:

You may refine your search by editing the current search expression or entering new one in the text box.

☐ Check to search within this result set

Results Key:
JNL = Journal or Magazine **CNF** = Conference **STD** = Standard

1 The peak limiting of a baseband code-division multiplexed signal applied to a predistorted power amplifier
Mizuta, S.; Kawaguchi, H.; Akaiwa, Y.;

Vehicular Technology Conference, 2001. VTC 2001 Spring. IEEE VTS

53rd , Volume: 3 , 6-9 May 2001

Pages:1953 - 1957 vol.3

[\[Abstract\]](#) [\[PDF Full-Text \(268 KB\)\]](#) IEEE CNF

2 On the degradation of OFDM-signals due to peak-clipping in optimal predistorted power amplifiers
Friese, M.;

Global Telecommunications Conference, 1998. GLOBECOM 98. The Bridge to C Integration. IEEE , Volume: 2 , 8-12 Nov. 1998

Pages:939 - 944 vol.2

[\[Abstract\]](#) [\[PDF Full-Text \(340 KB\)\]](#) IEEE CNF

3 Threshold IBO of HPA in the Predistorted OFDM Communication Systems
Ryu, H.-G.; Park, J.S.; Park, J.-S.;

Broadcasting, IEEE Transactions on , Volume: 50 , Issue: 4 , Dec. 2004

Pages:425 - 428

[\[Abstract\]](#) [\[PDF Full-Text \(424 KB\)\]](#) IEEE JNL

4 Optimum design of a predistortion RF power amplifier for multicarrier WCDMA applications
Jeonghyeon Cha; Jaehyok Yi; Kim, J.; Bumman Kim;

Microwave Theory and Techniques, IEEE Transactions on , Volume: 52 , Issue 2 , Feb. 2004

Pages:655 - 663

[\[Abstract\]](#) [\[PDF Full-Text \(440 KB\)\]](#) IEEE JNL

5 Improvement of power efficiency of HPA by the PAPR reduction and predistortion

Heung-Gyoon Ryu; Tran Phuong Hoa; Kang Mi Lee; Sang-Woo Kim; Jin-Soo P
Consumer Electronics, IEEE Transactions on , Volume: 50 , Issue: 1 , Feb 200
Pages:119 - 124

[\[Abstract\]](#) [\[PDF Full-Text \(661 KB\)\]](#) IEEE JNL

6 Improved data predistortion and trellis coded modulation for the bandlimited nonlinear satellite link

Lim, J.-H.; Gelfand, S.B.; Krogmeier, J.V.;
MILCOM 2000. 21st Century Military Communications Conference
Proceedings , Volume: 2 , 22-25 Oct. 2000
Pages:1089 - 1093 vol.2

[\[Abstract\]](#) [\[PDF Full-Text \(464 KB\)\]](#) IEEE CNF

7 A simplified predistorter for compensation of nonlinear distortion in OFDM systems

Sekchin Chang; Powers, E.J.;
Global Telecommunications Conference, 2001. GLOBECOM '01. IEEE , Volume
5 , 25-29 Nov. 2001
Pages:3080 - 3084 vol.5

[\[Abstract\]](#) [\[PDF Full-Text \(363 KB\)\]](#) IEEE CNF

8 Thermal memory effects modeling and compensation in RF power amplifiers and predistortion linearizers

Boumaiza, S.; Ghannouchi, F.M.;
Microwave Theory and Techniques, IEEE Transactions on , Volume: 51 , Issue
12 , Dec. 2003
Pages:2427 - 2433

[\[Abstract\]](#) [\[PDF Full-Text \(479 KB\)\]](#) IEEE JNL

9 Realistic power-amplifiers characterization with application to baseband digital predistortion for 3G base stations

Boumaiza, S.; Ghannouchi, F.M.;
Microwave Theory and Techniques, IEEE Transactions on , Volume: 50 , Issue
12 , Dec. 2002
Pages:3016 - 3021

[\[Abstract\]](#) [\[PDF Full-Text \(547 KB\)\]](#) IEEE JNL

10 An FET-level linearization method using a predistortion branch FET

Min-Gun Kim; Chung-Hwan Kim; Hyun-Kyu Yu; Jaejin Lee;
Microwave and Guided Wave Letters, IEEE [see also IEEE Microwave and Wire
Components Letters] , Volume: 9 , Issue: 6 , June 1999
Pages:233 - 235

[\[Abstract\]](#) [\[PDF Full-Text \(56 KB\)\]](#) [IEEE JNL](#)

11 Compensation of nonlinear distortions with memory effects in digit transmitters

Wang, T.; Ilow, J.;

Communication Networks and Services Research, 2004. Proceedings. Second Annual Conference on , 19-21 May 2004

Pages:3 - 9

[\[Abstract\]](#) [\[PDF Full-Text \(368 KB\)\]](#) [IEEE CNF](#)

12 Low-IF 5 GHz WLAN linearized transmitter using baseband digital predistorter

Helaoui, M.; Boumaiza, S.; Ghazel, A.; Ghannouchi, F.M.;

Electronics, Circuits and Systems, 2003. ICECS 2003. Proceedings of the 2003 IEEE International Conference on , Volume: 1 , 14-17 Dec. 2003

Pages:260 - 263 Vol.1

[\[Abstract\]](#) [\[PDF Full-Text \(1574 KB\)\]](#) [IEEE CNF](#)

13 A consideration of phase distortion in linear power amplification of QPSK and two tone sinusoidal stimuli

Staudinger, J.;

Wireless Communications Conference, 1997., Proceedings , 11-13 Aug. 1997

Pages:105 - 109

[\[Abstract\]](#) [\[PDF Full-Text \(360 KB\)\]](#) [IEEE CNF](#)

14 A 174 W high-efficiency GaN HEMT power amplifier for W-CDMA base station applications

Joshin, K.; Kikkawa, T.; Hayashi, H.; Maniwa, T.; Yokokawa, S.; Yokoyama, M. Adachi, N.; Takikawa, M.;

Electron Devices Meeting, 2003. IEDM '03 Technical Digest. IEEE International 10 Dec. 2003

Pages:12.6.1 - 12.6.3

[\[Abstract\]](#) [\[PDF Full-Text \(273 KB\)\]](#) [IEEE CNF](#)

15 Doherty amplifier with DSP control to improve performance in CDM operation

Yu Zhao; Iwamoto, M.; Larson, L.E.; Asbeck, P.M.;

Microwave Symposium Digest, 2003 IEEE MTT-S International , Volume: 2 , 8 June 2003

Pages:687 - 690 vol.2

[\[Abstract\]](#) [\[PDF Full-Text \(335 KB\)\]](#) [IEEE CNF](#)

[1](#) [2](#) [Next](#)

LAST - (Unfiled) - 11

File View Edit Tools Window Help

Drafts

ISBA:

BRS:

BRS:

ISBA:

Pending

Active

12:16:1 another and peak ad (reducing or reduction or reduce or reducer) and predist

Faded

amplifier and peak ad) reduc\$ and predistortion

Saved

Favorites

Tagged (0)

UDC

Queue

Trash

Search

US-PUB,USPAT,USDOB,EPO,JP,GER,ENT,IPM,TPR

Default processor OR

amplifier and peak ad) (reducing or reduction or reduce or reducer) and predistortion

BRS form

ISAR form

Image

Text

HTML

	U	I	Document ID	Issue Date	Pages	Title	Current OR	Current XRef	Retrieval Classif	Inventor	S	C	P	Re	In	
1	<input type="checkbox"/>	<input type="checkbox"/>	US 20040123224 A1	20040624	6	Method and circuit for controlling the peak power of a filtered signal in a single carrier data transmission system	714/781			Colombo, Alessandro et al.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	US
2	<input type="checkbox"/>	<input type="checkbox"/>	US 20040052314 A1	20040318	31	Crest factor reduction processor for wireless communications	375/296			Copeland, Gregory C.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	US
3	<input type="checkbox"/>	<input type="checkbox"/>	US 20040005014 A1	20040108	16	System and method for adjusting a power level of a transmission signal	375/295			Talwar, Shipa et al.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	US
4	<input type="checkbox"/>	<input type="checkbox"/>	US 6314146 B1	20011106	49	Peak to average power ratio reduction	375/346	375/285; 455/296		Telado, Jose et al.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	US
5	<input type="checkbox"/>	<input type="checkbox"/>	US 5675285 A	19971007	11	Multichannel predistortion linearizer for multiple amplifiers with multiple antennas	330/124R	330/149; 330/295		Winters, Jack H.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	US
6	<input type="checkbox"/>	<input type="checkbox"/>	US 5608760 A	19970304	9	Method and circuits for the transmission and reception of numeric signals, in which the peak power of the filtered signal is controlled and reduced	375/285	329/304; 375/261; 375/260		Sandri, Andrea et al.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	US

HRs

Details

HTML

Ready